

AND INDEPENDENT RESURVEY  
Survey of Portion of W. Boundary of T. 8 N., R. 30 E.

CHAINS Over level land, covered with sage.

2.90 Wash, drains NE.,

40.00 Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap marked

$\frac{1}{4}$   
S12 S7  
1919

Raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

49.50 Road, bears NW. and SE.

69.00 To bank of Walker Lake.

Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in the ground, for meander cor. of fracl. secs. 7 and 12, with brass cap marked

MC  
S12 S7  
R29E R30E  
T8N  
1919

Raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.

Land, level.

Soil, gravelly to sandy.

Timber, none.

Undergrowth, sage.

ESTABLISHMENT OF CORNERS ON N. BOUNDARY OF T. 8 N., R. 30 E.

Corners for subdivisions in T. 8 N., R. 30 E., were set at regular intervals East longitudinally from the west boundary of the township as follows:

At easting of 280.00 chs. from the W. boundary of this township, and  $4.9\frac{1}{4}$  chs. from meander cor. for fracl. secs. 3 and 34.

Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor. sec. 3, with brass cap marked

$\frac{1}{4}$  S3

1919

No stone for mound; pits impracticable.