

SURVEY OF THE SEVENTH STANDARD PARALLEL NORTH THRU RANGE 26 EAST.

chains

This cor. stands on west edge of dry wash, 12 ft. deep, course S.

Land, rolling and broken.

Soil, sandy clay covered with a layer of small gravel; 3rd rate.

Undergrowth, greasewood.

From the Std. cor. of secs. 35 and 36.

East,

Over mountainous land, ascending SW slope thru scattering undergrowth 30 ft. to

18.30 Spur, slopes S., desc. 150 ft. over SE slope to

36.900 Dry wash, course SE. Thence over sandy and gravelly flat.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for Std. $\frac{1}{4}$ sec. cor. of sec. 36, with brass cap mkd:

	SC
$\frac{1}{4}$ S	36

1920

and raise a mound of stone, 3 ft. base, 1 $\frac{1}{2}$ ft. high, N. of cor.

80.00 Set an iron post, 3 ft. long, 3 ins. diam., 26 ins. in the ground, for Std. cor. of T. 36 N., Rs. 26 and 27 E. with brass cap mkd:

	SC
T 36 N	
R 26 E	R 27 E
S 36	S 31

1920

and raise a mound of stone, 3 ft. base, 1 $\frac{1}{2}$ ft. high, N. of Cor.

Land, W. half mile, mountainous; E. half, rolling and flat.

Soil, hard gravelly, 3rd rate.

Undergrowth, greasewood.
