SURVEY OF THE SEVENTH STANDARD PARALLEL NORTH THRU RANGE 27 EAST.

	chains	
	80,00	Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in
		the ground, for Std. cor. of secs. 35 and 36, with
		brass cap mkd:
-		T 36 N R 27 E \$ 35 S 36
		1920
		dig pits, 18x18x12 ins., N., E. and W. of cor., 3 ft.
	-	dist.
	-	Land, level.
		Soil, sandy alkaline clay, 3rd rate.
		No vegetation.
	0.230	From the Std. cor. of secs. 35 and 36,
The second second second	and the second s	East,
	ta orienta girina ad Again	Over level desert land,
The second second second	and the second s	Difference between measurements of 40.00 chs., by two
-		measurements, is 2 lks., position of middle point
		by 1st measurement = 39.99 chs.,
		by 2nd measurement = 40.01 chs.,
And in contrast of the last of		the mean of which is
- Commentered and a second	40.00	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in
DESCRIPTION OF STREET,		the ground, for Std, $\frac{1}{4}$ sec. cor. of sec. 36, with
Manager of Street of Street		brass cap mkd
on the state of the same of the same of		SC \frac{1}{4} S 36
-	*	
- Constitution of the last		1920
-		dig pits, 18x18x12 ins., E. amd W. of cor., 3 ft. dist.
- Contractor of Contractor	_	No difference between measurements of 80.00 chs., by two
		measurements,
BURBURA BALALORAGIANIA	80.00	Set an iron post, 3 ft. long, 3 ins. diam., 26 ins. in
designation of the second		the ground, for Std. cor. of T. 36 N., Rs. 27 and 28 E
-		with brass cap mkd:
ACTUAL CONTRACTOR		T 36 N R 27 E R 28 E
Street, or other parties		S 36 S 31 \
-		1920
STREET, STREET		dig pits, 18x18x12 ins., N., E. and W. of cor., 3 ft.
1		

dist.