

## SURVEY OF THE SEVENTH STANDARD PARALLEL NORTH THRU RANGE 28 EAST.

chains

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for Std,  $\frac{1}{4}$  sec. cor. of sec. 33, with brass cap mkd:

$$\begin{array}{c} \text{SC} \\ \frac{1}{4} \text{ S } 33 \end{array}$$

1920

dig pits, 18x18x12 ins., E. and W. of cor., 3 ft. dist  
Difference between measurements of 80.00 chs., by two measurements, is 1 lk., position of middle point

by 1st measurement = 79.99 $\frac{1}{2}$ chs.,

by 2nd measurement = 80.00 $\frac{1}{2}$  chs.,

the mean of which is

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for Std. cor. of secs. 33 and 34, with brass cap mkd:

$$\begin{array}{c} \text{SC} \\ \text{T } 36 \text{ N } \mid \text{R } 28 \text{ E} \\ \text{S } 33 \mid \text{S } 34 \end{array}$$

1920

dig pits, 18x18x12 ins., N., E. and W. of cor., 3 ft. dist.

Land, level.

Soil, sandy alkaline clay, 3rd rate.

Undergrowth, greasewood.

From the Std. cor. of secs. 33 and 34,

East,

Over level desert land,

20.00 W. edge of low sand dunes, bears N. and S. Thence over rolling sand hills,

35.00 E. edge of sand dunes, bears N. and S. Continue over level desert land.

No difference between measurements of 40.00 chs., by two measurements,

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in ground, for Std.  $\frac{1}{4}$  sec. cor. of sec. 34, with brass cap mkd:

$$\begin{array}{c} \text{SC} \\ \frac{1}{4} \text{ S } 34 \end{array}$$

1920