

SURVEY OF THE SEVENTH STANDARD PARALLEL NORTH THRU RANGE 28 EAST.

chains

the ground, for Std. cor. of secs. 35 and 36, with
brass cap mkd:

	SC	
T 36 N		R 28 E
S 35		S 36

1920

dig pits, 18x18x12 ins., N., E. and W. of cor., 3 ft.
dist.

Land, level.

Soil, sandy alkaline clay, 3rd rate.

Undergrowth, greasewood.

From the Std. cor. of secs. 35 and 36,

East,

Over slightly rolling land thru scattering undergrowth

8.00 Low spur, slopes S.

10.50 Oil prospect hole, bears S., 90 lks. dist.

Difference between measurements 40.00 chs., by two
measurements, is 4 lks., position of middle point

by 1st measurement = 39.98 chs.,

by 2nd measurement = 40.02 chs.,

the mean of which is

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in
the ground, for Std. $\frac{1}{4}$ sec. cor. of sec. 36, with
brass cap mkd:

	SC
$\frac{1}{4}$ S 36	

1920

dig pits, 18x18x12 ins., E. and W. of cor., 3 ft.
dist.

No difference between measurements of 80.00 chs., by
two measurements,

80.00 Set an iron post, 3 ft. long, 3 ins. diam., 26 ins. in
the ground, for Std. cor. of T. 36 N., Rs. 28 and
29 E., with brass cap mkd: