SURVEY OF THE SEVENTH STANDARD PARALLEL NORTH THRU RANGE 28 EAST.

chains

T 36 N R 28E | R29 E S 36

1920

dig pits, 18x18x12 ins., N., E. and W. of cor., 3.ft. dist.

Land, W. 20 chs., rolling; 60 chs., level.

Soil, sandy and gravelly clay, 3rd rate.

Undergrowth, greasewood.

SURVEY OF PART OF THE SOUTH BDY. OF T. 35 N., R. 31 E.

From the cor. of secs. 31 and 32, on the south bdy. of T. 35 N., R. 31 E., which is a lava stone, 8x10x8 ins. above ground, mkd. and witnessedd as described by the surveyor general,

West, on true line,

Over rolling land, descending gradual W. slope thru scattering undergrowth,

7.75 Intersect the closing corner of T. 34 N., Rs. 30 and 31 E., which is an iron post, 3 ins. diam., 12 ins. above ground, mkd. and witnessed as described by the surveyor general.

> From cor., Mining cabin, E. end, bears S.8°17'W., 8.00 chs., dist.

Mining cabin, W. end, bears S.12°19'W., 8.65 chs. dist E. end of shaft house, 16x30 ft., bears S., 1.30 chs.

Road, bears NW and SE. 14.96

Road, bears NW and SE. 18.00

Dry wash, 10 ft. wide, 4 ft. deep, course NW. 20.14

Road, bears NW and SE. 20.40

Head of dry wash, course NE. 37.00

> Set an iroh post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor. of sec. 31, with brass cap mkd:

40.00

13.50