

of a portion
 RETRACEMENT/OF THE NORTH BDY. OF TOWNSHIP 36 NORTH, RANGE 26 EAST.

chains

From the cor. of Ts. 36 and 37 N., Rs. 25 and 26 E.,
 previously described,

East, on retracement, searching for original corners at
 record distances, none of which were found.

319.37 At record distance from the cor. of Ts. 36 and 37 N.,
 Rs. 25 and 26 E.,

Set an iron post, 3 ft. long, 2 ins. diam., 8 ins. in
 the ground to bedrock, in a mound of stone, for the
 restored cor. of secs. 2, 3, 34 and 35, with brass
 cap mkd:

T 37 N		R 26 E
S 34		S 35
S 3		S 2
		T 36 N
		1920

 SURVEY OF A PORTION OF THE N. BDY. T 36 N., R. 26 E. M.D.M.

From the cor. of secs. 2, 3, 34 and 35,

East, on random line,

160.00 Intersect the Range line bet. Rs. 26 and 27 E., at a
 point 515.81 chs. N. of the Std. cor. of T. 36 N., Rs.
 26 and 27 E., at which point

Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in
 the ground, for cor. of Ts. 36 and 37 N., Rs. 26 and
 27 E., with brass cap mkd:

T 37 N		
R 26 E		R 27 E
S 36		S 31
S 1		S 6
		T 36 N
		1920

and raise a mound of stone, 3 ft. base, $1\frac{1}{2}$ ft. high,
 S. of cor.

Thence

West, on true line,

Over mountainous land, asc. NE. slope 130 ft. thru
 scattering undergrowth,

18.40 Spur, slopes N. Desc. 80 ft. over broken NW. slope

39.80 Dry wash, course N.