

16 Dependent Resurvey of the Fifth Standard Parallel N., through R. 24 E.

Chains

N. and S.

41.00 To mean high water level of Winnemucca Lake, at which point,

Set an iron post, 3 ft. long, 1 in. dia., 27 ins. in the ground, for standard meander cor. on S. bdy. sec. 32, with brass cap mkd.

S C
T26N
R24E
S32
MC
1924

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, E. of cor.

Land, rolling. Soil, light sandy loam, mixed with coarse gravel and granite boulders 4th rate. A narrow strip of fine sand free from rocks about 4.00 chs. wide parallels the shore of Winnemucca Lake. Undergrowth, scrub sagebrush, shadscale, salt brush and a scant growth of grass. No timber. The present waters edge is 4 ft. below the standard meander cor. and W. 2.80 chs. dist.

Survey of the East Boundary of T. 26 N., R. 24 E.

From the standard cor. of T. 26 N., Rs. 24 and 25 E., heretofore described.

North, bet. secs. 31 and 36.

Over rough mountainous land, through dense undergrowth, asc. 65 ft. over rocky SE. slope.

6.20 Top of rocky spur, extends E. about 3.00 chs. forming a small rocky peak, whence spur extends about 8.00 chs. NE. to a higher peak 100 ft. above this contour. This same spur extends W. about 10.00 chs. forming a peak of granite outcropping 225 ft. above this contour. Thence desc. abruptly 115 ft. over NW. slope.

11.00 Head of gulch, course NW.; desc. 125 ft. over SW. slope.

18.00 Low point of spur, slopes W.; desc. 105 ft. over NW. slope.