Survey of the East Boundary of T. 26 N., R. 24 E. Chains Deposit a granite stone, 8x4x2 ins., mkd. with a cross (X), at base of post. 44.80 Hillside drain, 10 ft. below & sec. cor., course W.; asc. 5 ft. to. 48.70 Point of rocky spur, slopes W.; desc. 90 ft. to 58.70 Gulch, course W.; asc. 130.ft. to 68.80 Top of spur, projects W.; desc. 110 ft. to 78.40 Gulch, course N. 80° W.; asc. 15 ft. to 80.00 Set an iron post, 3 ft. long, 2 ins. dia., 27 ins. in the ground, for cor. of secs. 1, 6, 7 and 12, with brass cap mkd. T26N R24E | R25E dig pits, 18x18x12 ins., NE., SE., SW. and NW. of post 3 ft. dist. No stones available for mound. Land, rough broken mountainous. Soil, light sandy clay I loam, dry, shallow and mixed with decomposed granite. 4th rate. Undergrowth, sagebrush, buckbrush and a fair growth of bunch grass. Fine grazing. No timber. North, bet. secs. 1 and 6. Over rough mountainous land, through dense undergrowth, desc. gradually over broad ridge. . 10.00 Top of broad divide ridge, bears H. and W.; desc. 35 ft. Gulch, course N. 70° W.; desc. 15 ft. to 15.00 Point of spur, slopes N. 80° W.; desc. 10 ft. to 20.00 30.00 Gulch, course W.; desc. 15 ft. to. Point of spur, slopes N. 70° W.; desc. 10 ft. to 38.70 Set an iron post, 3 ft. long, 1 in. dia., 27 ins. in the 40.00 ground, for \frac{1}{2} sec. cor., with brass cap mkd. . S 1 S 6 and raise a mound of stone, 2 ft. base, 1 ft. high,

W. of cor.