

Chains

$$\begin{array}{c} \text{MC} \diagup \text{T27N} \\ \text{S } 4 \text{ --- R24E} \\ \text{MC} \diagdown \text{T26N} \\ \text{1924} \end{array}$$

and raise a mound of stone, 4 ft. base, 3 ft. high,
E. of cor.

Land, rolling. Soil, light sandy loam, mixed with coarse
gravel and boulders. strongly alkaline; 4th rate. Un-
dergrowth, sagebrush, saltbrush, greasewood and a scant
growth of grass. No timber. Distance to present water
level is 50.48 chs. and is 15 ft. below meander cor.

Subdivisions of T. 26 N., R. 24 E.

From the standard cor. of secs. 35 and 36, on the S. bdy.
of the tp., heretofore described.

N. 0° 01' W., bet. secs. 35 and 36.

Over rough mountainous land, through dense undergrowth,
desc. 225 ft. over series of small ledges and outcrop-
ping along SW. slope.

10.70 Ravine, channel, 25 lks. wide, with perpendicular banks
5 ft. high, gravel bottom, course S. 70° W.; asc.
abruptly 540 ft. over rocky gravelly S. slope.

36.90 Top of spur, projects SE.; desc. 15 ft. to

38.55 A point determined through operation hereinafter recorded
which has a southing of 40.00 chs. from the cor. of
secs. 25, 26, 35 and 36, on the Sectional Correction
line, hereinafter described. At this point,
Set an iron post, 3 ft. long, 1 in. dia., 27 ins. in the
ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ \text{S } 35 \text{ | } \text{S } 36 \\ \text{1924} \end{array}$$

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high,
W. of cor.

40.20 Gulch, 15 ft. below $\frac{1}{4}$ sec. cor., course SE.; asc. 75 ft.

43.00 Gulch, course S. 10° W.; asc. 230 ft. over rocky S. slope.

50.90 Top of high rocky spur ridge, bears N. 60° E. about 5.00
chs. dist. forming a circular rocky peak and about