


Chains



and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high,
E. of cor.


Land, rolling. Soil, light fine sand mixed with fine gravel.
No undergrowth, No timber. The distance to the present
waters edge of Winnemucca Lake from this meander cor.
is 18.43 chs., and 16 ft. below meander cor.

From the cor. of secs. 4, 5, 8 and 9.

N. $0^{\circ} 03'$ W., on a true line bet. secs. 4 and 5.

Over a gently sloping barren sandy and gravel beach, desc.
13 ft. to

13.32 To mean high water level of Winnemucca Lake at which point,
Set an iron post, 3 ft. long, 1 in. dia., 27 ins. in the
ground, for meander cor. for frac. secs. 4 and 5, with
brass cap mkd.



and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high,
S. of cor.

Land, rolling. Soil, light fine sand and fine gravel.
No undergrowth. No timber. The distance to the present
waters edge of Winnemucca Lake from the meander cor is
13.62 chs., and 15 ft. below meander cor.

Meanders of T. 27 N., R. 24 E.

From the meander cor. of frac. secs. 4 and 33, on the
N. bdy. of the Tp., heretofore described. Thence with
meanders in sec. 4.

Along sandy gravel beach.

S. $13^{\circ} 00'$ W. 16.00 chs.

S. $17^{\circ} 30'$ W. 8.00 "

S. $19^{\circ} 45'$ W. 13.00 "