


Survey of a Portion of the E. Bdy. of T. 26 N., R. 25 E.

Chains

Beginning at the cor. of secs. 19, 24, 25 and 30, set under Group No. 13, on the E. Bdy. of T. 26 N., R. 25 E., which I find to be a granite stone, 6x12x12 ins. above the ground, firmly set, dimly mkd., with 4 notches on N. and 2 notches on S. edges and witnessed by faint traces of pits. I now remonument this cor. as follows: Alongside the granite stone; Set an iron post, 3 ft. long, 2 ins. dia., 27 ins. in the ground, for cor. of secs. 19, 24, 25 and 30, with brass cap mkd.




Dig pits, 18x18x12 ins., NE., SE., SW., and NW., of post, 3 ft. dist. The new pits sufficiently obliterate the old ones. Thence

North, bet. secs. 19 and 24.

Over rolling mountainous land, desc. 6 ft. over NW. slope.

- 7.70 Ravine, course SW.; asc. 95 ft. over SE. slope.
- 16.90 Top of spur, projects W. about 3.00 chs.; thence SW.; desc. 10 ft.
- 19.40 Gulch, course SW.; asc. 115 ft. over SW. slope.
- 36.20 Top of spur, bears NE. and SW.; desc. gradually 20 ft. to
- 40.00 Set an iron post, 3 ft. long, 1 in. in dia., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.



and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor. Thence desc. gradually 35 ft. over SW. slope.

- 45.00 Top of Granite Spring Range, bears N. 10° W. and S. 10° E., desc. gradually 55 ft. over NE. slope.
- 60.00 Head of ravine, course E.; asc. 25 ft. over SE. slope.
- 70.00 Top of spur ridge, bears N. 40° E. and S. 40° W.; desc. 45 ft. over N. slope.
- 80.00 Set an iron post, 3 ft. long, 2 ins. in dia., 14 ins. in the ground to solid rock, and erect a mound of stone,