

Chains

at a point, 7.01 chs. S. 7° E. of cor. No. 2, which is a sawed pine post, 4 ins. sq., $2\frac{1}{2}$ ft. above ground, in a mound of earth and stone, scribed 2-2704-B.1; and 4-2704-B.4, facing their respective lodes.

75.82

Intersect the E. Bdy. of T. 12 N., R. 24 E., at a point, 1.80 chs. South of cor. of Tps. 12 and 13 N., Rs. 24 and 25 E., which is a granite stone, 12x10x8 ins. firmly set in a mound of stone, mkd. with 6 notches on 4 faces. I now change the markings on this cor. so that same refers to Tps. 12 and 13 N., R. 24 E. only.

At the point of intersection,

Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground, for closing cor. of Tps. 12 and 13 N., R. 25 E., with brass cap mkd.

T12N	T13N	
	R25E	
S1	S31	
	S 6	CC
R24E	T12N	
	1921	

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, E. of cor.

Land, rough mountainous. Soil, light shallow sandy and gravel on porphyry base rock, surface covered with loose baked cap rock of limestone formation. Undergrowth, sagebrush and shadscale and a scant growth of grass. No timber. Copper indications were observed along this line.

Retracement of East Boundary T. 13 N., R. 24 E.

Preliminary to the reestablishment of the W. Bdy. I retrace said lines, making diligent search for old cors. at 40.00 and 80.00 chs. and setting temp. points. When an old cor. or recognized property cor. is reached I return along the line and adjust all points to distances proportional to those of the original survey.
