

Subdivisions of T. 13 N., R. 25 E.

Chains

medium texture, dry and rocky. Undergrowth, sagebrush and shadscale, very little grass. Mineral indications were observed along this line.

From the cor. of secs. 19, 20, 29 and 30,  
West, on a true line, bet. secs. 19 and 30.

Over rolling mountainous land, asc. over rocky E. slope.

9.10 Top of detached butte, 100 ft. above sec. cor., projects E.; desc.

18.80 Base of depression, 20 ft. below top of butte, drains SE.; thence asc. rough mountainous land, over rocky E. slope.

19.28 Electric Power line, bears N. 3° E. and S. 3° W.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$  S-19  
S 30  
1921

and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N. of cor. This cor. stands 180 ft. above depression.

50.00 Point of spur, 275 ft. above  $\frac{1}{4}$  sec. cor., projects NE.; desc.

54.00 Gulch, 80 ft. below point of spur, course NE.; asc.

61.15 Same gulch course S. 85° E. 20 ft. above previous crossing, ascend 400 ft. to

75.40 Intersect the W. Bdy. of the Tp., at a point, 0.96 chs. N. 0° 08' E. of cor. of secs. 24 and 25, T. 13 N., R. 24 E. previously described. At the point of intersection,

Set an iron post, 3 ft. long, 2 ins. diam., 10 ins. in the ground to bed rock, and 14 ins. in a mound of stone, for closing cor. of secs. 19 and 30, with brass cap mkd.

T13N  
S24 | T13N  
S30 | S19  
R24E | R25E CC  
1921

and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, E. of cor.

Land, rolling and rough mountainous. Soil, light sandy