

Dependent Resurvey of the W. Bdy. of T. 12 N., R. 34 E.

Chains From the temporary point for the cor. of Ts. 11 and 12 N., Rs. 33 and 34 E; previously set South 240.00 chs. dist. from the old cor. of secs. 13 and 18, 19 and 24, T. 12 N., R. 33 and 34 E., W. 6.49 chs. and N. $1^{\circ} 33'$ E; 6.06 chs., ^{The} proportionate point for the cor. of Ts. 11 and 12 N., Rs. 33 and 34 E., set an iron post, 3 ft. long, 3 ins. in dia., 27 ins. in the ground, for the cor. of Ts. 11 and 12 N., Rs. 33 and 34 E., with brass cap mkd.

T12N	
R33E	R34E
S36	S31
S1	S6
T11N	
1921	

and raise a mound of stone, 2 ft. base $1\frac{1}{2}$ ft. high S. of the cor. Thence N. $1^{\circ} 33'$ E., on a true line, bet. secs. 31 and 36. Ascend gradual S. slope over nearly level land. Dry wash, course S.W., from E. The proportionate distance.

1.00
39.005

Set an iron post, 3 ft. long, 1 in. in diam., 8 ins. in the ground to solid rock, in a mound of stone, for the $\frac{1}{4}$ sec. cor. of sec. 31, with brass cap mkd.

$\frac{1}{4}$ S31
1921

40.30 Top of spur, 35 ft. above $\frac{1}{4}$ sec. cor., projects S.E. Desc. N.E. slope.

52.00 Dry wash, 190 ft. below spur, course E.

62.00 Top of spur, 208 ft. above wash, projects E.

72.30 Dry wash, 108 ft. below spur, course E.

77.00 Top of spur, 50 ft. above wash, projects E.

78.01 The proportionate distance. Set an iron post, 3 ft. long, 2 ins. in dia., 27 ins. in the ground, for the cor. of secs. 30 and 31, with brass cap mkd.

T12N	T12N
R33E	S30
S36	S31
	R34E
1921	

50 ft. above wash.

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high E. of the cor.

Land slightly rolling on S. half mile, rolling mountainous