

Subdivisions of T. 12 N., R. 33 E.

Chains.	From the cor. of secs. 1, 2, 35 and 36, on the S.bdy. of Twp. North, on a sectional guide meridian, bet. secs. 35 and 36.
	Ascend S.E. slope over rolling land.
4.90	Top of spur, 75 ft. above sec. cor., projects S.W.
12.00	Top of spur, 46 ft. above spur, projects S.E., from N.E.
16.90	Head of dry wash, 45 ft. below spur, course N.E.
23.00	Top of spur, 62 ft. above wash, projects W.
40.00	Set an iron post, 3 ft. long, 1 in. in dia., 16 ins. in the ground, to solid rock, in a mound of stone, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.
	<div>S35^{$\frac{1}{4}$}S36</div> <div>1921</div>
	68 ft. below spur.
65.50	Top of spur, 315 ft. above $\frac{1}{4}$ sec. cor., projects N.W.
75.00	Dry wash, 160 ft. below spur, course W.
79.68	Set an iron post, 3 ft. long, 2 ins. in dia., 14 ins. in the ground, in a mound of stone, for the witness cor. of secs. 25, 26, 35 and 36, with brass cap mkd.
	<div>WC</div> <div>T12N R33E</div> <div>S26 S25</div> <div>S35 S36</div> <div>1921</div>
80.00	True point for cor. falls in edge of wash, impracticable to set cor.
	Land, rolling mountainous. Soil, sandy and rocky.
	Undergrowth, scattering greasewood.

	From the true point for the cor. of secs. 25, 26, 35 and 36,
	East, on a true line, bet. secs. 25 and 36.
	Ascend W. slope over rolling land.
4.50	Dry wash, 2 chs. wide, 10 ft. deep, course N. 70° W.
	Asc. 100 ft.
18.00	Same wash, course S. 70° W. Asc. 90 ft.
31.50	Same was h, course N. 70° W.
40.00	Set an iron post, 3 ft. long, 1 in. in dia., 10 ins. in