

Subdivisions of T. 12 N., R. 33 E.

Chains. the ground, in a mound of stone, for the  $\frac{1}{4}$  sec. cor., with brass cap mkd.

S25  
 $\frac{1}{4}$ -----  
S36  
1921

100 ft. above wash.

47.60 Top of ridge, 275 ft. above  $\frac{1}{4}$  sec. cor., bears N.W. and S.E.

66.00 Head of wash, 350 ft. below ridge, course S.E.

73.30 Top of spur, 50 ft. above wash, projects S.E. Desc. E. slope 150 ft..

82.45 Intersect W. Bdy. of sec. 30, at a point, 2.07 chs., N. 1° 33' E., from the cor. of secs. 30 and 31, hereinbefore described.

Set an iron post, 3 ft. long, 2 ins. in dia., 27 ins. in the ground, for the closing cor. of secs. 25 and 36, with brass cap mkd.

T12N | T12N  
c. S25 |  
c. S36 | R34E  
R33E | S30  
1921

and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$  ft. high, W. of the cor.

Land, rough mountainous. Soil, sandy and rocky.

Undergrowth, scattering greasewood.

-----  
From the closing cor. of secs. 25 and 36,

S. 1° 33' W., on a true line.

2.07 The cor. of secs. 30 and 31, hereinbefore described.

40.04 Set an iron post, 3 ft. long, 1 in. in dia., 10 ins. in the ground, to solid rock, in a mound of stone, for the  $\frac{1}{4}$  sec. cor. of sec. 36, with brass cap mkd.

$\frac{1}{4}$  |  
S36 |  
1921 |

-----  
From the true point for the cor. of secs. 25, 26, 35 and 36,

North, on a sectional guide meridian, bet. secs. 25 and