Chains.

Set an iron post, 3 ft. long, 1 in. in dia., 10 ins. in the ground, to bed rock, in a mound of stone, for the  $\frac{1}{4}$  sec. cor., with brass cap mkd.

40 ft. above wash.

45.60 Top of ridge, 175 ft. above  $\frac{1}{4}$  sec. cor., bears N. and S.

48.60 Head of wash, 70 ft. below ridge, course N.E.

50.00 Base of vertical ledge, 30 ft. below wash, 100 ft. high, faces N.E. Desc. abrupt N.E. slope. 400 ft.

84.21 Intersect W. Bdy. of sec. 19, at a point, 3.99 chs.,

N. 1° 33' E. from the cor. of secs. 19 and 30, hereinbefore described.

Set an iron post, 3 ft. long, 2 ins. in dia., 27 ins. in the ground, for the closing cor. of secs. 24 and 25, with brass cap mkd.

and raise a mound of stone, 2 ft. base,  $l^{\frac{1}{2}}$  ft. high, W. of the cor.

Land, rolling mountainous. Soil, sandy and rocky. Undergrowth, scattering greasewood.

From the closing cor. of secs. 24 and 25, S. 1° 33' W., on a true line.

3.99 The cor. of secs. 19 and 24, hereinbefore described.

39.965 Set an iron post, 3 ft. long, 1 in. in dia., 27 ins. in the ground, for the \( \frac{1}{4} \) sec. cor. of sec. 25, with brass cap mkd.

and raise a mound, of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high,  $\overline{w}$ , of the cor.