

Survey of a Portion of Subdivisions of T. 45 N., R. 30 E.

Chains
 58.00 Gulch, course NE.; asc. 35 ft. to
 66.80 Point of spur, projects NE.; desc. 350 ft. to
 79.70 Gulch, course NE.; asc. 50 ft. to
 82.92 Intersect the Ninth Standard Parallel North, at a point,
 11.50 chs. E. of the standard cor. of secs. 34 and 35,
 which is an iron post, 2 ins. diam., 12 ins. above the
 ground, firmly set mkd. and witnessed as described by
 the surveyor general. At the point of intersection,
 Set an iron post, 3 ft. long, 2 ins. diam., on solid rock,
 24 ins. in a mound of stone with 4 ft. base, for closing
 cor. of secs. 2 and 3, with brass cap mkd.

T46N R30E

S35

S3

S2

T45N R30E

C/C

1921

At base of cor. marked a cross(X) on solid rock.
 Land, rough mountainous. Soil, light sandy clay mixed
 with coarse granite gravel and rocks, many granite
 outcrops and loose boulders. Undergrowth, sagebrush
 and shadscale.

Dependent Resurvey of a Portion of Subdivisions of
 T. 45 N., R. 30 E.

From the reestablished cor. of secs. 14, 15, 22 and 23,
 heretofore described.

West, on a true line, bet. secs. 15 and 22.

Over rough mountainous land, through dense undergrowth,
 asc. over S. slope. 370 ft. to

12.60 Point of spur, projects S.; desc. 70 ft. to

17.30 Gulch, course S. 20° E.; asc. 95 ft. to

26.10 Point of spur, projects S.; desc. 185 ft. to

34.00 Gulch, course S. 20° E.; asc. 65 ft. to

40.00 At record distance,

Set an iron post, 3 ft. long, 1 in. diam., 18 ins. in
 the ground to bed rock, and 8 ins. in a mound of stone,
 for $\frac{1}{4}$ cor. of secs. 15 and 22, with brass cap mkd.