

Dependent Resurvey of a Portion of Subdivisions of T. 37 N., R. 19 E. 17

Chains

line on E. Bdy. of sec. 3.

Asc. over broken SW. slope 10 ft. to

43.00 Point of low spur, projects SW.; desc. 15 ft. to

58.00 Dry wash, course SW.; asc. 30 ft. to

65.00 Point of low spur, projects SW.; desc. 10 ft. to

78.00 Head of wash, course S. 70° W.; asc. 20 ft. to

86.16 The cor. of secs. 2, 3, 34 and 35, on N. Bdy. of Tp.,
heretofore described.

Land, rolling. Soil, light sandy shallow clay loam, 3rd
rate. Very rocky. Vegetation, small scrub sagebrush
and a fair growth of grass.

Subdivisions of T. 37 N., R. 19 E.

From the cor. of secs. 11 and 12, heretofore described.

North, on a Sectional Guide Meridian, bet. secs. 11 and
12.

Over mountainous land, through dense undergrowth, desc.
30 ft. to

6.30 Cherry Creek, 10 lks. wide, 3 ins. deep, pure water,
course S. 35° W.; asc. 30 ft. to

11.40 Road, bears N. 35° E. and S. 35° W.; thence asc. 50 ft. to

14.40 Center of same road, in bend, bears NE. and SE.; asc.
165 ft. over rocky S. slope to

22.85 Top of spur, projects S. 10° W.; thence continue ascen-
ding along SW. slope. 270 ft. to

40.00 Set an iron post, 3 ft. long, 1 in. dia., 12 ins. in the
ground, to bed rock and 14 ins. in a mound of stone,
for $\frac{1}{4}$ sec. cor., with brass cap mkd.

S11 S12

1922

Deposit a small stone, mkd. (X) at base of monument.

Thence continue ascending along steep SW. slope 155 ft. to

51.75 Top of spur, S. 70° W.; desc. 160 ft. to

59.10 Deep gulch, course S. 80° W.; asc. 270 ft. to