

Dependent Resurvey of the South Boundary of T. 42 N., R. 28 E.

17

Chains

S. $89^{\circ} 42'$ W., on S. bdy. of sec. 31.
Over rough mountainous land, through dense undergrowth,
desc. 50 ft. over N. slope.

5.75 Head of gulch, course N.; asc. 30 ft.

10.40 Ravine, dry, course N. 70° E.; asc.

12.96 Proportionate distance.

Set an iron post, 3 ft. long, 2 ins. dia., 20 ins. in the
ground to solid rock, and 4 ins. in a mound of stone,
for cor. of secs. 5 and 6, with brass cap mkd.

$$\begin{array}{c} T42N R28E \\ S31 \\ \hline S 6 | S 5 \\ T41N | R28E \\ 1922 \end{array}$$

At base of monument deposit a granite stone, 6x6x6 ins.,
mkd. with a cross (X).

Thence asc. 160 ft. to

25.00 Point of low spur, projects S. 70° E.; desc. 10 ft. to

29.15 Same ravine, dry, course S. 70° E.; asc. 315 ft. over NE.
slope.

40.00 Set an iron post, 3 ft. long, 1 in. dia., 12 ins. in the
ground to solid rock and 14 ins. in a mound of stone,
for $\frac{1}{4}$ cor. of sec. 31, with brass cap mkd.

$$\frac{1}{4} S 31$$

1922

At base of monument deposit a granite stone, 5x4x2 ins.,
mkd. with a cross (X).

Thence asc. abruptly 215 ft. over NE. slope.

49.70 Top of abrupt ascent; bears N. and S.; thence asc. gradu-
ally 60 ft. to

54.58 Proportionate distance.

Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the
ground, for $\frac{1}{4}$ sec. cor. of sec. 6, with brass cap mkd.

$$\frac{1}{4} S 6$$

1922

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, S.
of cor.