

Chains

West, on a true line, on N. bdy. of sec. 6.  
Over rough mountainous land, through dense undergrowth,  
asc. 10 ft. to

11.50 Top of spur, bears N. and S. 30° W.; desc. 640 ft. to

26.60 Ravine, course N. 20° W.; asc. 70 ft. to

30.20 Top of spur, bears NW. and SE.; desc. 200 ft. to

40.00 Set an iron post, 3 ft. long, 1 in. dia., 14 ins. in the  
ground to solid rock and 12 ins. in a mound of stone,  
for 1/4 cor. of sec. 6, with brass cap mkd.

1/4 S 6  
1922

At base of monument deposit a granite stone, 4x4x2 ins.,  
mkd. with a cross (X).

Thence continue to descend over rocky broken SW. slope.  
310 ft. to

61.15 Head of gulch, course NW.; asc. 10 ft. to

62.55 Point of rocky spur, projects N.; desc. 90 ft. to

64.90 Gulch, course SW.; asc. 160 ft. to

76.50 Point of rocky spur, projects S.; desc. 75 ft. to

84.00 Head of gulch, course S.; asc. 45 ft. to

88.50 Top of spur, bears N. 20° W. and S. 20° E.; desc. 90 ft.  
to

92.55 Intersect the E. Bdy. of T. 43 N., R. 27 E., at a point,  
18.54 chs. N., of the reestablished cor. of Tps. 42  
and 43 N., R. 27 E., heretofore described. At the point  
of intersection,

Set an iron post, 3 ft. long, 3 ins. dia., 16 ins. in the  
ground to solid rock and 8 ins. in a mound of stone,  
for closing cor. of Tps. 42 and 43 N., R. 28 E., with  
brass cap mkd.

T43N | T43N  
R28E | R28E  
S36 | S31  
S 6 | S 6 - CC  
R27E | T42N  
1922

At base of monument deposit a granite stone, 5x4x3 ins.,  
mkd. with a cross (X).

J. H. ...  
321