

Dependent Resurvey

Resurvey of a Portion of the West Boundary of T. 44 N., R. 30 E. 15

Chains

cribed by the surveyor general. I now change the markings on brass cap so as to refer to secs. 6 and 7, R. 30 E. only, as follows:

T44N	T44N
R29E	S 6
S25	S 7
	R30E
1921	

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, E. of cor. Destroyed the mound of stone W. of cor.

North, on W. bdy. sec. 6.

39.75 Intersect the $\frac{1}{4}$ cor. of secs. 1 and 6, which is an iron post, 1 in. dia., 10 ins. above the ground, mkd. and witnessed as described by the surveyor general. I now change the markings on brass cap so as to refer to sec. 6 only, as follows:

$\frac{1}{4}$ S 6

1921

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, E. of cor. Destroyed the mound of stone W. of cor.

80.72 Intersect the cor. of Ts. 44 and 45 N., Rs. 29 and 30 E., which is an iron post, 3 ins. dia., 12 ins. above the ground, firmly set, mkd. and witnessed as described by the surveyor general. I now change the markings on brass cap so as to refer to Ts. 44 and 45 N., R. 30 E. only, as follows:

	T45N
T44N	R30E
R29E	S31
S24	S 6
	T44N
1921	

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, E. of cor. Destroyed the mound of stone S. of cor.

Dependent

Resurvey of a Portion of the West Boundary of T. 45 N.,

R. 30 E.

From the cor. of Ts. 44 and 45 N., R. 30 E. heretofore referred to