

Dependent Resurvey

18 Resurvey of a Portion of the West Boundary of T. 45 N., R. 30 E.

Chains

North, on W. Bdy. sec. 18.

40.10 Intersect the $\frac{1}{4}$ cor. of secs. 13 and 18, which is an iron post, 1 in. dia., 10 ins. above the ground, firmly set, mkd. and witnessed as described by the surveyor general. I now change the markings on brass cap so as to refer to sec. 18, only as follows:

$\frac{1}{4}$ S 18
 1921

Raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, E. of cor.
 Destroyed the mound of stone, W. of cor.

80.10 Intersect the cor. of secs. 7, 12, 13 and 18, which is an iron post, 2 ins. dia., 24 ins. above the ground, surrounded by a mound of stone, firmly set, mkd. and witnessed as described by the surveyor general. I now change the markings on brass cap so as to refer to secs. 7 and 18 only, as follows:

T45N | T45N
 R29E | 37
 S36 | S18
 R30E
 1921

From which,

A rock cliff, 4 ft. high, facing S. bears N. 33 lks. dist.

John
227

mkd. B O
 X

Defaced markings of bearing object on W. side of line,
 Raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, E. of cor.

 Survey of the East Boundary of T. 44 N., R. 29 E.

From the cor. of Ts. 43 and 44 N., R. 29 E., heretofore described.

North, on E. bdy. sec. 36.

Over rough mountainous land, through scattering timber,
 asc. 140 ft. over general NE. slope to point of spur.

5.00 Leave scattering timber, bears NW. and SE.

13.70 Point of spur, projects E.; desc. over NE. slope.

17.29 The cor. of secs. 7 and 18, T. 44 N., R. 30 E., heretofore described.