

Chains
55.90 Saddle in spur ridge, bearing E. and W. ; desc. 360 ft.
over rocky broken NW. slope.
56.89 Intersect the $\frac{1}{4}$ cor. of sec. 19, T. 45 N., R. 30 E.,
heretofore described.
76.00 Head of ravine, course NW.; continue to desc. over general
NW. slope, 40 ft. to
80.00 Set an iron post, 3 ft. long, 2 ins. dia., 20 ins. in the
ground to solid rock and 4 ins. in a mound of stone,
for cor. of secs. 1 and 12, with brass cap mkd.

T44N	T45N
S 1	R30E
S12	S19
R29E	

1921

At base of monument deposit a small granite stone, 6x4x4
ins. mkd. with a cross (X).
Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
Land, rough mountainous. Soil, light sandy clay loam,
shallow and decomposed granite with loose rock and
numerous granite outcroppings, 3rd rate. Undergrowth,
sagebrush and buckbrush and a fair growth of grass.
Timber, aspen.

North, on E. Bdy. of sec. 1.
Over rough mountainous land, through dense undergrowth,
Desc. 180 ft. over broken NW. slope to

12.30 Head of gulch, course NW.; continue to desc.
16.68 Intersect the cor. of secs. 18 and 19, T. 45 N., R. 30 E.,
heretofore described.
27.00 Ravine, course SW.; asc. 70 ft. over SW. slope to $\frac{1}{4}$ sec.
cor.
28.20 Dim road, bears NE. and SW.; thence asc. over S. slope.
40.00 Set an iron post, 3 ft. long, 1 in. dia., 26 ins. in the
ground, for $\frac{1}{4}$ cor. of sec. 1, with brass cap mkd.

$\frac{1}{4}$ S 1
1921

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, E. of cor.