

Dependent Resurvey of a portion of the W. Bdy. of T. 46 N., R. 31 E.

Chains.

$\frac{1}{4}$
 S1
 1923

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of the cor.

From the $\frac{1}{4}$ sec. cor. for sec. 1, with continuous measurement N. $0^{\circ} 35'$ E., on a true line.

43.00 Top of spur, 20 ft. above $\frac{1}{4}$ sec. cor., projects E.
Desc. NE. slope.

71.50 Dry wash, 50 ft. below spur, course E.

79.70 Dry wash, 10 ft. below wash, course SE.
Asc. S. slope 10 ft. to

82.93 Intersect the cor. of Ts. 46 and 47 N., Rs. 30 and 31 E., hereinbefore described.

Land, rolling. Soil, sandy and rocky clay loam.

Undergrowth, medium growth of sage and scattering bunch grass.

Start

Dependent Resurvey of a portion of the E. Bdy. of T. 46 N., R. 31 E.

All corners set at record distances on this resurvey.

From the St. cor. of Ts. 46 N., Rs. 31 and 32 E., hereinbefore described,

North, on a true line, bet. secs. 31 and 36.

2.50 Dry wash, course S. E.
Asc. SE. slope over rough mountainous land.

40.00 Set an iron post, 3 ft. long, 1 in. in dia., 14 ins. in the ground, to solid rock, in a mound of stone, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.

$\frac{1}{4}$
 S36 | S31
 1923

Deposit a granite stone, 8 x 6 x 4 ins., with cross marked (x) at base of post.

52.00 Top of ridge, 150 ft. above $\frac{1}{4}$ sec. cor., bears NE. and SW.
Desc. abrupt NW. slope. 470 ft. to

80.00 Set an iron post, 3 ft. long, 2 ins. in dia., 15 ins. in the ground, to solid rock, in a mound of stone,