

Survey of a portion of the subdivisions of T. 46 N., R. 31 E.

Chains.

Asc. SW. slope.

84.10 Small spring bears E., 50 lks. dist.

91.21 Intersect the S. Bdy. of T. 47 N., R. 31 E., at a point,
S. $89^{\circ} 33'$ W., 14.53 chs. dist., from the cor. of
secs. 35 and 36, which is an iron post, 2 ins. in dia.,
firmly set and properly marked and witnessed as described
in the field notes of T. 47 N., R. 31 E.

Set an iron post, 3 ft. long, 2 ins. in dia., 27 ins.
in the ground, for the closing cor. of secs. 1 and 2,
with brass cap mkd.

T47N R31E
S35

S2	S1
T46N	R31E
C	C
1923	

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, S.
of the cor. Cor. stands on SW. slope 150 ft. above wash.
Land, rolling and rough mountainous. Soil, sandy and
rocky. Undergrowth, good growth of sage and grass.
Timber, dense aspen and willows along creeks and ravines.

From the closing cor. of secs. 1 and 2, hereinbefore
described,

N. $89^{\circ} 33'$ E., on a true line, on the N. Bdy. of sec. 1.

14.53 The cor. of secs. 35 and 36, hereinbefore described.

Thence East, on a true line, on the N. Bdy. of sec. 1.

39.94 Set an iron post, 3 ft. long, 1 in. in dia., 10 ins. in
the ground, to solid rock, in a mound of stone, for the
 $\frac{1}{4}$ sec. cor. for sec. 1, with brass cap mkd.

$\frac{1}{4}$ S1
1923

Deposit a granite stone, 8 x 6 x 3 ins., with cross
marked (x), at base of post.
