

Survey of a portion of the subdivisions of T. 46 N., R. 31 E.

Chains.	
44.10	Dry wash, 120 ft. below $\frac{1}{4}$ sec. cor., course NE. Asc. SE. slope.
51.50	Top of spur, 100 ft. above wash, projects NE. Desc. N. slope.
87.10	Dry wash, 530 ft. below spur, course NE. Asc. SE. slope 120 ft. to
90.22	Intersect the S. Bdy. of T. 47 N., R. 31 E., at a point, S. $89^{\circ} 33'$ W., 9.87 chs. dist., from the cor. of secs. 34 and 35, which is an iron post, 2 ins. in dia., firmly set and properly marked and witnessed, as described in the field notes of T. 47 N., R. 31 E. Set an iron post, 3 ft. long, 2 ins. in dia., 12 ins. in the ground, to solid rock, in a mound of stone, for the closing cor. of secs. 2 and 3, with brass cap mkd.
	<div style="text-align: center;"> T47N R31E S34 <hr style="width: 100px; margin: 0 auto;"/> S3 S2 T46N R31E C C 1923 </div>
	Deposit a granite stone, 15 x 8 x 6 ins., with cross marked (x) at base of post. Land, rough mountainous. Soil, sandy and rocky. Undergrowth, medium growth of sage and bunch grass. Timber, aspen and mahogany.

	From the closing cor. of secs. 2 and 3, N. $89^{\circ} 33'$ E., on a true line, on the N. Bdy. of sec. 2.
9.87	The cor. of secs. 34 and 35, hereinbefore described.
39.83	Set an iron post, 3 ft. long, 1 in. in dia., 20 ins. in the ground, to solid rock, in a mound of stone, for the $\frac{1}{4}$ sec. cor. for sec. 2, with brass cap mkd.
	<div style="text-align: center;"> $\frac{1}{4}$ S2 1923 </div>
	Deposit a granite stone, 8 x 6 x 3 ins., with cross marked (x), at base of post.
