

## Dependent Resurvey of a portion of the S. Bdy. of T. 47 N., R. 31 E.

## Chains.

Alongside, set an iron post, 3 ft. long, 2 ins. in dia., 24 ins. in the ground, to solid rock, in a mound of stone, and deposit a stone with cross marked (x) at base of post, for the cor. of secs. 35 and 36, with brass cap mkd.

T47N | R31E  
S35 | S36  
T46N | R31E  
1922

Land, rough mountainous with numerous outcroppings of granite. Soil, rocky and sandy.

Undergrowth, bunch grass and sage.

## Survey of the S.Bdy. of sec. 36, T.47 N., R. 31 E.

From the cor. of secs. 35 and 36,

East, on a true line, on the S.Bdy. of sec. 36.

Asc. rocky S.W. slope over rough mountainous land.

5.00 Top of spur, 80 ft. above sec. cor.

Desc. S.E. slope.

32.00 Head of wash, 80 ft. below spur, course S.W.

Asc. S.W. slope 140 ft. to

40.00 Set an iron post, 3 ft. long, 1 in. in dia., 27 ins.

in the ground, for the  $\frac{1}{4}$  sec. cor., with brass cap mkd.

$\frac{1}{4}$  S36

1922

Raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N. of the cor.

Asc. along S.W. slope of ridge 720 ft. to

84.55 Intersect E. Bdy. of twp., determined by a previous retracement, at a point, N.  $0^{\circ} 22'$  W., 7.62 chs dist., from the old cor. of Ts. 46 and 47 N., Rs. 31 and 32 E., hereinafter described.

Set an iron post, 3 ft. long, 3 ins. in dia., 27 ins.

in the ground, for the closing cor. of Ts. 46 and 47

N., R. 31 E., with brass cap mkd.