

Dependent resurvey of the old subdivisions of T. 47 N., R. 31 E.

Chains.

81.66 Intersect the old cor. of secs. 4 and 5, 32 and 33, which is a granite stone, 10 x 16 x 24 ins., firmly set in a mound of stone, marked 4 notches on E. face and 2 notches on W. face. Alongside, set an iron post, 3 ft. long, 2 ins. in dia., 27 ins. in the ground, for the cor. of sec. 5, with brass cap mkd.

T47N
S5 | S4
S5
R31E

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

94.16 Intersect the Nevada-Oregon State Line, at a point, S. $89^{\circ} 11'$ W., 29.86 chs. dist. from the 229th Mile Post. Set an iron post, 3 ft. long, 2 ins. in dia., 27 ins. in the ground, for the closing cor. of secs. 4 and 5, with brass cap mkd.

ORE
S5 | S4
T47N | R31E
cc
1922

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, S. of the cor.

Land, slightly rolling. Soil, sandy and gravelly.

Undergrowth, sage and bunch grass.

From the N.E. cor. of original sec. 5, N. $88^{\circ} 21'$ W., on a true line, on the N. Bdy. of original sec. 5.

Desc. N.W. slope over rolling land.

4.80 Head of dry wash, 20 ft. below sec. cor. course N.

Asc. N.E. slope.

9.00 Top of low spur, 40 ft. above wash, projects N.

Desc. N.W. slope 80 ft. to

42.05 The proportionate point.

Set an iron post, 3 ft. long, 1 in. in dia., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.