Dependent resurvey	of the old	subdivisions o	f T.	47 N.,	R. 31 E.

Chains. Set an iron post, 3 ft. long, 1 in. in dia., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor. for sec. 6, with brass cap mkd. Dig pits, 18 x 18 x 12 ins., on line, N. and S. of post, 3 ft. dist. 41.60 The proportionate point. Set an iron post, 3 ft. long, 1 in. in dia., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor. for sec. 5, with brass cap mkd. 1922 Dig pits, 18 x 18 x 12 ins., on line, N. and S. of post, 3 ft. dist. Road, bears S. 20° W. and N. 20° E. 62.80 Intersect the N.W. cor. of original sec. 5, hereinbefore 83.71 described. Intersect the Nevada-Oregon State Line, at a point, 92.56 S. 89° 11' W., 33.46 chs. dist. from the 230th Mile Post. Set an iron post, 3 ft. long, 2 ins. in dia., 27 ins. in the ground, for the closing cor. of secs. 5 and 6, with brass cap mkd. S6 S5 T47N R31E Raise a mound of stone, 2 ft. base, 12 ft. high, S. of the cor. Land, slightly rolling. Soil, sandy and gravelly. Undergrowth, sage, shadscale and bunch grass.

> From the closing cor. of secs. 5 and 6, N.89° 11' E., on a true line, on the N. Bdy. of sec. 5. Intersect the 230th Mile Post.

33.46