

Dependent resurvey of the old subdivisions of T. 47 N., R. 31 E.

Chains.

- 40.01 A northing of 40.00 chs.
Set an iron post, 3 ft. long, 1 in. in dia., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor. for sec. 6, with brass cap mkd.
- | $\frac{1}{4}$
| S6
1922
- Dig pits, 18 x 18 x 12 ins., N. and S. of post, 3 ft. dist.
-
- From the cor. of secs. 25 and 26, 35 and 36, East, on a resurvey, bet. secs. 25 and 36. Asc. N.E. slope over rolling mountainous land.
- 4.60 Fence, bears S. and N.W.
- 22.50 Top of spur, 180 ft. above sec. cor., projects N.W. Desc. N.E. slope.
- 25.00 Fence, bears, S. 70° W. and N.
- 40.00 The record distance
Set an iron post, 3 ft. long, 1 in. in dia., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with brass cap mkd.
- S25
 $\frac{1}{4}$ ———
S36
1922
- Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of the cor. Cor. stands on N.E. slope 30 ft. below spur. Thence continue East on a survey of the East $\frac{1}{2}$ mile bet. secs. 25 and 36.
- 47.50 Dry wash, 50 ft. below $\frac{1}{4}$ sec. cor. course N. Asc. N. slope.
- 56.20 Fence, bears N.E. and S.W.
- 61.40 Little Wilder creek, 50 ft. above wash, running water, 2 lks. wide, 2 ins. deep, course N.W. Asc. along S.W. slope 70 ft. to
- 79.49 Intersect East Bdy. of Twp., at a point, N. 1° 08' W., 6.14 chs. dist. from the cor. of secs. 30 and 31, hereinbefore described.
- Set an iron post, 3 ft. long, 2 ins. in dia., 27 ins. in the ground, for the closing cor. of secs. 25 and 36,