

Survey of a portion of the subdivisions of T. 47 N., R. 31 E.

Chains.

67.20 Head of dry wash, 400 ft. below spur, course S.E.

Asc. S.W. slope 170 ft. to

76.81 Intersect the E. Bdy. of twp., at a point, S. 1° 37' E.,
14.49 chs. dist. from the cor. of secs. 6 and 7, herein-
before described.

Set an iron post, 3 ft. long, 2 ins. in dia., 14 ins.
in the ground, to solid rock, in a mound of stone, and
deposit a stone with cross marked (x) at base of post,
for the closing cor. of secs. 1 and 12, with brass cap
marked.

	T47N	
C	S1	T47N
c	S12	S7
	R31E	R32E
	1922	

Land, rough mountainous. Soil, sandy and rocky.

Undergrowth, sage and bunch grass.

From the closing cor. of sec. 1 and 12,
S. 1° 37' E., on a true line, on the E. Bdy. of sec. 12.
31.43 Intersect the $\frac{1}{4}$ sec. cor. for sec. 7, hereinbefore
described.

40.04 Set an iron post, 3 ft. long, 1 in. in dia., 27 ins.
in the ground, for the $\frac{1}{4}$ sec. cor. for sec. 12, with
brass cap mkd.

	$\frac{1}{4}$
S12	
1922	

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of
the cor.

From the closing cor. of secs. 1 and 12,
N. 1° 37' W., on a true line, on the E. Bdy. of sec. 1.
14.49 Intersect the cor. of secs. 6 and 7, hereinbefore
described.

40.02 A northing of 40.00 chs.
Set an iron post, 3 ft. long, 1 in. in dia., 12 ins.
in the ground, to solid rock, in a mound of stone, and