

Survey of a portion of the subdivisions of T. 47 N., R. 31 E.

Chains.	
48.90	Dry wash, 20 ft. below $\frac{1}{4}$ sec. cor., course S. 60° W. Asc. S.W. slope.
76.00	Top of spur-ridge, 130 ft. above wash, bears N.W. and E. Desc. N.E. slope.
82.20	Dry wash, 150 ft. below spur-ridge, course N.W. Asc. S.W. slope.
95.00	Top of spur-ridge, 60 ft. above wash, bears N.W. and S.E. Desc. N.E. slope.
108.50	Dry wash, 160 ft. below spur-ridge, course N.W. Asc. S.W. slope 70 ft. to
114.34	Intersect the Nevada-Oregon State Line, at a point, S. $89^{\circ} 15'$ W., 27.67 chs. dist. from the 227th Mile Post. Set an iron post, 3 ft. long, 2 ins. in dia., 27 ins. in the ground, for the closing cor. of secs. 2 and 3, with brass cap mkd.

ORE
 S3 | S2
 T47N | R31E
 c | c
 1922

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, S.
of the cor.

Land, rolling mountainous. Soil, sandy and gravelly.

Undergrowth, sage and bunch grass.

27.67	From the closing cor. of secs. 2 and 3, N. $89^{\circ} 15'$ E., on a true line, on the N. Bdy. of sec. 2. Intersect the 227th Mile Post. Thence N. $89^{\circ} 17'$ E., on a true line.
40.17	Set an iron post, 3 ft. long, 1 in. in dia., 18 ins. in the ground, to solid rock, in a mound of stone, and deposit a stone with cross marked (x) at base of post, for the $\frac{1}{4}$ sec. cor. for sec. 2, with brass cap mkd.

ORE
 S2
 1922

From the closing cor. of secs. 2 and 3,

S. $89^{\circ} 15'$ W., on a true line, on the N. Bdy. of sec. 3.