

TEST OF INSTRUMENT T. 27 N., R. 37 E.

Measurements are made with a 5 ch. Lallie Steel Tape, tested by comparison with a Lufkin Standard Steel Tape, and measurements are reduced to true horizontal distances by the use of clinometers.

CHAINS INDEPENDENT RESURVEY OF E. BOUNDARY OF T. 27 N., R. 37 E.

I begin at the cor. of Tps. 26 and 27 N., Rs. 37 and 38 E., which is a stone, firmly set in a mound of stone, and marked and witnessed as described by the Surveyor General, alongside of which I

Set an iron post, 3 ft. long, 3 ins. in dia., 24 ins. in the ground, for the cor. of Tps. 26 and 27 N., Rs. 37 and 38 E., with brass cap marked

T27N	
R37E	R38E
S36	S31
S1	S6
T26N	
1922	

Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, S. of cor.

Thence

North, on a random line setting temp. $\frac{1}{4}$ sec. and sec. cors, at regular intervals of 40.00 and 80.00 chs., and at

484.87 Intersect N. bdy. of the twp. 5.55 chs. W. of the cor. of Tps. 27 and 28 N., T. 37 E., which is a 3 in. iron post, firmly set in the ground, and marked and witnessed as described by the Surveyor General; I change markings to read for T. 28 N., R. 37 E., only, as follows:

T28N	
R37E	
S36	
S6	
T27N	R38E
1922	

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, NW. of cor.

From the cor. of Tps. 26 and 27 N., Rs. 37 and 38 E.

North, on true E. bdy. of sec. 36

Ascend gentle SE. slope over rolling mountainous land