

INDEPENDENT RESURVEY OF E. BOUNDARY OF T. 27 N., R. 37 E.

CHAINS
80.00

Set an iron post, 3 ft. long, 2 ins. in dia., 12 ins. in the ground, to solid rock, over a marked stone, surrounded by a mound of stone, for the cor. of secs. 1, 6, 7 and 12, with brass cap marked

T27N	
R37E	R38E
S1	S6 ✓
S12	S7
1922	

Land, rolling. Soil, sandy. Timber, none.

Undergrowth, sage. General drainage, SE.

North, on true E. boundary of sec. 1

Over rolling land

.66 The old cor. of secs. 1, 6, 7 and 12, which is a stone, firmly set in a mound of stone, and marked and witnessed as described /by the Surveyer General, bears W. 1.46 chs. I destroy all traces of same

7.50 Dry wash, drains SE.

40.00 Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked

$\frac{1}{4}$	
S1	S6 ✓
1922	

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

40.63 Old $\frac{1}{4}$ sec. cor., which is a stone, firmly set in a mound of stone, and marked and witnessed as described by the Surveyor General, bears W. 1.93 chs. I destroy all traces of same

42.10 Dry wash, drains SE. Ascend about 115 ft. to

59.20 Low spur, projects E.

67.80 Draw, drains SE.