SURVEY	OF	W.	BOUNDARY	OF	T.	24	N.,	R.	45	E.
MOTE A TOTAL	0.2				_		,		. /	

		SURVEY OF W. BOUNDARY OF T. 24 N., R. 45 E.
	CHAINS	I begin at the cor. of Ts. 23 and 24 N., Rs. 44 and 45
		E. (latitude 39° 56' N., and longitude 116° 59' W.),
		which is a 3 in. iron post, firmly set in the ground,
		and marked and witnessed as described by the Surveyor
		General
		Thence
		North, on W. bdy. of sec. 31
		Over rolling land
	13.20	Dry wash, drains NW.
	40.00	Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in
		the ground, for \frac{1}{4} sec. cor., with brass cap marked
		$\frac{1}{4}$
	• • • • • • • • • • • • • • • • • • •	s36 s31
		1922
		Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
	53.40	Bed of Hall Creek(dry)drains NW., 33 ft. below \frac{1}{4} sec. cor.
	72.10	Old road, bears NW. and SE.
200	80.00	Set an iron post, 3 ft. long, 2 ins. in dia., 24 ins. in
		the ground, for the cor. of secs. 25, 30, 31 and 36,
		with brass cap marked T24N
	***	R\$25 B\$5E
		S36 S31
		1922
		Raise a mound of stone, 2 ft. base, 1 ft. high, W. of cor.
	9	Land, rolling. Soil, sandy. Timber, none.
		Undergrowth, sage. General drainage, NW.
		North, on W. bdy. of sec. 30
	The Lake	Over rolling land
	22.50	Old road, bears E. and W.
	40.00	Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in
		the ground, for 2 sec. cor., with brass cap marked
		\$25\\$30
		1922
	w w	Raise a mound of stone, 2 ft. base, 1 ft. high, W. of cor.
	80.00	Set an iron post, 3 ft. long, 2 ins. in dia., 24 ins. in

the ground, for the cor. of secs. 19, 24, 25 and 30,