

SURVEY OF W. BOUNDARY OF T. 24 N., R. 45 E.

CHAINS

$$\frac{1}{4}$$

S1	S6
1922	

Dig pits crosswise on line, N. and S. of cor.

78.50 Dry wash, drains NW.

80.00 Set an iron post, 3 ft. long, 3 ins. in dia., 24 ins. in the ground, for the cor. of Ts. 24 and 25 N., Rs. 44 and 45 E., with brass cap marked

T25N	
R44E	R45E
S36	S31
S1	S6
T24N	
1922	

Dig four pits, one each on line North, East, South and West of cor.

Land, rolling. Soil, sandy. Timber, none.

Undergrowth, sage. General drainage, NW.

SURVEY OF E. BOUNDARY OF T. 24 N., R. 45 E.

From the cor. of Ts. 23 and 24 N., Rs. 45 and 46 E.,

which is a 3 in. iron post, firmly set in a mound of stone, and marked and witnessed as described by the Surveyor General

North, on E. bdy. of sec. 36

Ascend SW. slope over rolling mountainous land 77 ft. to

40.00 Set an iron post, 3 ft. long, 1 in. in dia., 12 ins. in the ground to solid rock, over a marked stone, surrounded by a mound of stone, for $\frac{1}{4}$ sec. cor., with brass cap marked
$$\frac{1}{4}$$

S36	S31
1922	

Descend steep NE. slope 132 ft. to

49.00 Head of draw, drains NW. Ascend SW. slope 96 ft. to

80.00 Set an iron post, 3 ft. long, 2 ins. in dia., 12 ins. in the ground to solid rock, over a marked stone, surrounded by a mound of stone, for the cor. of secs. 25, 30, 31 and 36, with brass cap marked