

## Subdivisions of T. 13 S., R. 47 E.

## Chains.

40.00 Set an iron post, 3 ft. long, 1 in. in dia., 18 ins. in the ground, in a mound of stone, for the  $\frac{1}{4}$  sec. cor., with brass cap mkd.

S2  
 $\frac{1}{4}$   
S11  
1921

400 ft. below sec. cor.,

61.00 Dry wash, 120 ft. below  $\frac{1}{4}$  sec. cor., course S.W.

70.00 Dry wash, 50 ft. below wash, course S.

70.90 Road, bears N.E. and S.W.

80.00 The cor. of secs. 2, 3, 10 and 11:

Land, E. half mile, rough mountainous; W. half mile, slightly rolling. Soil, rocky, sandy and clay loam of medium texture. Undergrowth, salt sage.

N.0° 01' W., on a true line, bet. secs. 2 and 3.

Ascend S.W. slope over rolling land.

15.00 Road, bears N.W. and S.E.

38.50 Top of spur, 272 ft. above sec. cor., projects S.E.

40.00 Head of dry wash, course S.E., 140 ft. above spur.

Set an iron post, 3 ft. long, 1 in. in dia., 27 ins. in the ground, for the  $\frac{1}{4}$  sec. cor., with brass cap mkd.

S3  
S2  
1921

and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high W. of the cor.

49.50 Top of ridge, 160 ft. above  $\frac{1}{4}$  sec. cor., bears N.E. and S.W.

65.50 Dry wash, 232 ft. below ridge, course N.W.

77.00 Dry wash, course S.W.

82.32 Intersect N.bdy. of twp., at a point, S.89° 57' W., 9.10 chs. dist. from the Stand. cor. of secs. 34 and 35, hereinbefore described.

Set an iron post, 3 ft. long, 2 ins. in dia., 18 ins. in the ground, in a mound of stone, for the closing cor. of