

Establishment of corners on W. Bdy. T. 20 N., R. 45 $\frac{1}{2}$ E.

At a point North 12.85 chs., from the $\frac{1}{4}$ sec. cor. of sec. 1, T. 20 N., R. 45 E., which is a 1-in. iron post, set, marked and witnessed, as described by the Surveyor General, and on gentle SE. slope

Set an iron post, 3 ft. long, 1 in. in dia., 10 ins. in the ground, to solid rock, in a mound of stone, for the $\frac{1}{4}$ sec. cor. of sec. 1, T. 20 N., R. 45 $\frac{1}{2}$ E., with brass cap mkd

$\frac{1}{4}$

S1

1924

At base of post deposit a marked(X)stone, 1x2x4 ins.

CHAINS

SURVEY OF E. BDY. T. 20 N., R. 45 $\frac{1}{2}$ E.

From the cor. of T. 20 N., Rs. 45 $\frac{1}{2}$ and 46 E., hereinbefore described

North bet. secs. 36 and 31

Desc. general NW. slope 85 ft. to

30.90 Desc. steep NW. slope 165 ft. to

40.00 Ont moderate NW. slope

Set an iron post, 3 ft. long, 1 in. in dia., 12 ins. in rocky ground, in a mound of stone, for $\frac{1}{4}$ sec. cor., with brass cap mkd

$\frac{1}{4}$

S36 | S31

1924

At base of post deposit a marked(X)stone, $\frac{1}{2}$ x3x5 ins.

Desc. steep broken NW. slope 250 ft. to 52.00

43.20 Top of ledge 35 ft. high, bears E. and W., facing N.

52.00 Desc. moderate NW. slope over numerous small washes and low spurs to

77.00 Thence across level land through dense sagebrush.

80.00 On level ground in high sagebrush

Set an iron post, 3 ft. long, 2 ins. in dia., 27 ins. in the ground, for the cor. of secs. 25, 30, 31 and 36, T. 20 N., Rs. 45 $\frac{1}{2}$ and 46 E., with brass cap mkd