

Survey of E. Bdy. T. 20 N., R. 45 $\frac{1}{2}$ E.

CHAINS

$$\begin{array}{c} \frac{1}{4} \\ | \\ S1 | S6 \\ | \\ 1924 \end{array}$$

Raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor.
Continue over rolling land

84.32 Intersect Fourth Standard Parallel S 89° 45' E., 9.28
chs. from the Standard $\frac{1}{4}$ sec. cor. of sec. 31, T. 21 N.,
R. 46 E., described in notes of survey of T. 20 N., R.
46 E., surveyed in conjunction with this township, and
at point of intersection

Set an iron post, 3 ft. long, 3 ins. in dia., 27 ins. in
the ground, for the closing corner of T. 20 N., Rs.
45 $\frac{1}{2}$ and 46 E., with brass cap mkd

$$\begin{array}{c} R46E \\ T21N \\ S31 \\ \hline S1 | S6 \\ R45\frac{1}{2}E | R46E \\ | \\ 1924 \\ CC \end{array}$$

Raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, S. of cor.
Land, gently rolling. Timber, none. Soil, gravelly loam.
Undergrowth, scattering sagebrush. General drainage, NE.
Poor grazing.

Dependent Resurvey of a portion of 4th Standard Parallel N.

From the standard $\frac{1}{4}$ sec. cor. of sec. 31, T. 21 N., R. 46
E.

West, on a random line retracing 4th Std. Parallel North.

40.42 Fall 7 lks. S. of the Std. cor. of T. 21 N., Rs. 45 and
46 E., which is a 3 in. iron post, set, marked and
witnessed, as described by the Surveyor General

The bearing of this half mile is therefor N 89° 54' W.,
and the distance 40.42. I return to the Std. $\frac{1}{4}$ sec. cor.
of sec. 31

Thence N 89° 54' W., on Dependent Resurvey of 4th Std.
Parallel North.

Over gently rolling land

30.72 Westing of 40.00 chs. from the closing cor. of T. 20 N.,
Rs. 45 $\frac{1}{2}$ and 46 E.