

Dependent Resurvey of a portion of 4th Standard Parallel N.

Chains Set an iron post, 3 ft. long, 1 in. in dia., 10 ins. in rocky ground, in a mound of stone, for $\frac{1}{4}$ sec. cor of sec. 1 only, with brass cap mkd

$\frac{1}{4}$ S1
1924

At base of post deposit a marked(X) stone, $\frac{1}{2} \times 2 \times 3$ ins.

40.42 Standard corner of T. 21 N., Rs 45 and 46 E., from which the closing cor. of T. 20 N., Rs. 45 and $45\frac{1}{2}$ E., bears N. $89^{\circ} 57'$ W., 3.84 chs. dist., and which is a 3 in. iron post, set, marked and witnessed, as described by the Surveyor General. I change markings on same to read:

T21NR45E
S36

S1 | S1
R45E | R45 $\frac{1}{2}$ E
T20N
1924

Subdivisions T. 20 N., R. 45 $\frac{1}{2}$ E

From the cor. of secs. 25, 30, 31 and 36, on E. bdy. of twp.

S. $89^{\circ} 58'$ W., on a random line bet. secs. 25 and 36

40.00 Set temp. $\frac{1}{4}$ sec. cor.

53.92 Intersect W. bdy. of the twp. 15 lks. S. of the cor. of secs. 25 and 36

Thence

S. $89^{\circ} 52'$ E., on true line bet. secs 25 and 36

Asc. moderate NW. slope 145 ft. to

13.92 On moderate NW. slope

Set an iron post, 3 ft. long, 1 in. in dia., 6 ins. in rocky ground, in a mound of stone, for $\frac{1}{4}$ sec. cor., with brass cap mkd

$\frac{1}{4}$ S25
S36
1924

At base of post deposit a marked(X) stone, $1 \times 3 \times 6$ ins.

Asc. steep rocky NW. slope 30 ft. to

15.90 Rocky ridge, bears SW. and NE. Thence along medium S. slope

20.90 Desc. steep rocky SE. slope 115 ft. to

28.60 Thence over rolling land

34.10 Wash, 8 lks. wide, 2 ft. deep, drains S. 35° W.