

DEPENDENT RESURVEY OF A PORTION OF FOURTH  
STANDARD PARALLEL NORTH

CHAINS	and on gentle N. slope
	Set an iron post, 3 ft. long, 1 in. dia., 8 ins. in rocky ground, in a mound of stone, for $\frac{1}{4}$ sec. cor. of sec. 6 only, with brass cap mkd
	$\frac{1}{4}$ S6 1924
	At base of post deposit a marked(X) stone, 1x4x6 ins.
80.57	Standard cor. of secs. 31 and 32
	Land, rolling. Soil, gravelly loam. Timber, none.
	Undergrowth, sagebrush. Poor grazing. General drainage, N.
	N. 89° 45' W., on dependent resurvey along S. bdy. sec. 31
	Over gently rolling land
13.20	Wash, 5 lks. wide, 6 ins. deep, drains N. 35° E.
29.70	Wash, 4 lks. wide, 6 ins. deep, drains N. 45° E.
31.16	Closing cor. of T. 20 N., Rs. 45 $\frac{1}{2}$ and 46 E., set in survey of E. bdy. T. 20 N., R. 45 $\frac{1}{2}$ E., made in conjunction with survey of this township
	Land, gently rolling. Soil, gravelly loam. Timber, none.
	Undergrowth, sagebrush. General drainage, N. Fair grazing.

INDEPENDENT RESURVEY OF A PORTION OF FOURTH STANDARD PARALLEL NORTH.

CHAINS	From the standard cor. of secs. 33 and 34
	East, on a random line along S. bdy. of sec. 34
40.37	Fall 6 lks. N. of old standard $\frac{1}{4}$ sec. cor.
	Thence on same line continuing measurement
80.79	Fall 12 lks. N. of old standard cor. of secs. 34 and 35
	Thence on same line continuing measurement
121.28	Fall 33 lks. N. of old standard $\frac{1}{4}$ sec. cor.
	Thence on same line continuing measurement
161.81	Fall 36 lks. N. of old standard cor. of secs. 35 and 36
	Thence on same line continuing measurement
202.01	Fall 39 lks. N. of old standard $\frac{1}{4}$ sec. cor.
	Thence on same line continuing measurement
240.00	Find no traces of old standard cor. of T. 21 N., Rs. 46 and 47 E.
251.06	Intersect W. bdy. of T. 21 N., R. 47 E., N. 0° 12' E. 3.49 chs. from the standard SW. cor. of T. 21 N., R. 47 E., set in conjunction with survey of this township; at point of intersection