

SUBDIVISIONS T. 20 N., R. 46 E.

CHAINS

83.13 Intersect 4th Std. Par. N., W. 4.46 chs. from  $\frac{1}{4}$  Std. Cor. Sec. 36  
 and at point of intersection  
 Set an iron post, 3 ft. long, 2 ins. dia., 6 ins. in  
 rocky ground, in a mound of stone, for closing cor. of  
 secs. 1 and 2, with brass cap mkd

T21N R46E

S2 | S1

CC

T20N

1924

At base of post deposit a marked (x) stone,  $\frac{1}{2} \times 2 \times 4$  ins.  
 Land, rolling mountainous. Soil, rocky and gravelly.  
 Timber, pinon. Undergrowth, sagebrush.  
 Fair grazing. General drainage, W.

From the cor. of secs. 2, 3, 34 and 35, on S. bdy. of tp.,  
 which is an iron post, firmly set in the ground, marked  
 and witnessed as described by the Surveyor General

Thence

N 0° 01' W., bet. secs. 34 and 35

Slight ascent of SE. slope

30.00 Thence along E. slope

35.00 Desc. 35 ft. down gentle NE. slope to

40.00 On gentle NE. slope

Set an iron post, 3 ft. long, 1 in. dia., 27 ins. in the  
 ground, for  $\frac{1}{4}$  sec. cor., with brass cap mkd

$\frac{1}{4}$

S34 | S35

1924

Raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

Slight descent

43.00 Slight ascent along gentle SE. slope

45.00 Desc. gentle NE. slope

52.90 Desc. NE. slope 95 ft. to draw

53.90 Enter aspen thicket

62.20 Draw, heads about 3 chs. W., drains W.

Asc. gentle SE. slope 95 ft. to cor.

68.00 Leave aspen thicket