

SUBDIVISIONS T. 20 N., R. 46 E.

CHAINS

40.00 Set an iron post, 3 ft. long, 1 in. dia., 12 ins. in the ground to solid rock, in a mound of stone, for $\frac{1}{4}$ sec. cor., with brass cap mkd

$\frac{1}{4}$
S3 | S2
1924

At base of post, deposit a marked (x) stone, 1x2x4 ins.

Over gently rolling land

83.29 Intersect 4th. Std. Par. N., W. 4.18 chs. from $\frac{1}{4}$ Std. Cor. Sec. 35 and at point of intersection Set an iron post, 3 ft. long, 2 ins. dia., 27 ins. in the ground, for the closing cor. of secs. 32 and 3, with

brass cap mkd

T21N R46E

S3 | S2

C8
T20N
1924

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high S. of cor.

Land, rolling. Soil, gravelly loam.

Timber, none. Undergrowth, sagebrush and shadscale

Fair grazing. General drainage, N.

From the cor. of secs. 33 and 34, on S. bdy. of tp.,

which is a 3 in. iron post, firmly set in the ground,

marked and witnessed as described by the Surveyor General

Thence

N 0° 02' W., bet. secs. 33 and 34

Desc. rocky NW. slope 115 ft. to

20.00 Asc. along gentle SW. slope

23.00 Dry wash, 10 lks. wide, 6 ins. deep, drains N 45° W.

33.60 Continue along SW. slope

40.00 On steep W. slope

Set an iron post, 3 ft. long, 1 in. dia., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd

$\frac{1}{4}$
S33 | S34
1924

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

Thence along W. slope

44.20 Desc. W. to NW. rocky slope 375 ft. to