SUBDIVISIONS T. 20 N. R. 46 E

CHAINS N 0° 02' W., bet. secs. 3 and 4

Desc. 80 ft. over rolling mountainous land to

10.40 Surface wash, drains N 55° W.

Surface wash, drains W. 18.10

Spur, slopes S 75° W. 28.20

Set an iron post, 3 ft. long, 1 in. dia., 27 ins. in the 40.00 ground, for 4 sec. cor., with brass cap mkd

1924

Raise a mound of stone, 2 ft. base, 12 ft. high, W. of cor.

Thence over rolling land

43.20 Surface wash, drains SW.

Edge of rolling mesa, bears E. and W. Intersect 4th Std. Part N., W. 4.40 chs. from \$\frac{1}{4}\$ Std. Cor. Sec. 34 and at point of intersection Set an iron post, 3 ft. long, 2 ins. dia., 10 ins. in rocky ground, in a mound of stone, for closing cor. of

secs. 3 and 4, with brass cap mkd

T21N R46E

.1924

At base of post deposit a marked(x)stone, 1x2x5 ins.

Land, rolling. Soil, gravelly and sandy,

Timber, none. Undergrowth, sagebrush and shadscale.

Fair grazing. General drainage, NW.

From the cor. of secs. 4, 5, 32 and 33, on S. bdy. of tp. which is a 3 in. iron post, firmly set in a mound of stone, marked and witnessed as described by the Surveyor General

N 0° 03' W., bet. secs. 32 and 33

Desc. rocky NW. slope 220 ft. to

13.80 Indian Creek, 6 lks. wide, 6 ins. deep, course N 75° W., good spring has its source about 25 chs. SE.

Asc. along SW. slope 65 ft. to

23.80 Rocky spur, projects NW. Desc. moderate NE. slope

Thence along general NW. slope