

## SUBDIVISIONS T. 20 N., R. 46 E.

## CHAINS

Set an iron post, 3 ft. long, 1 in. dia., 20 ins. in rocky ground, in a mound of stone, for  $\frac{1}{4}$  sec. cor., with brass cap mkd

$$\begin{array}{r} S 6 \\ \frac{1}{4} S 7 \\ \hline 1924 \end{array}$$

At base of post deposit a marked(x)stone,  $\frac{1}{2} \times 2 \times 4$  ins.

65.80 Dry wash, 10 lks. wide, 2 ft. deep, drains N  $10^\circ$  W. Asc. moderate SW. slope 60 ft. to 74.60.

68.50 Road, bears NW. and SE.

74.60 Thence over gently rolling land

79.01 Cor. of secs. 5, 6, 7 and 8

Land, rolling bench. Soil, gravelly loam.

Timber, none. Undergrowth, sagebrush and shadscale.

Fair grazing. General drainage, NW.

N  $0^\circ 03'$  W., bet. secs. 5 and 6

Slight descent of general NE. slope

40.00 On gentle NE. slope

Set an iron post, 3 ft. long, 1 in. dia., 15 ins. in rocky ground, in a mound of stone, for  $\frac{1}{4}$  sec. cor., with brass cap mkd

$$\begin{array}{r} \frac{1}{4} \\ S 6 \quad | \quad S 5 \\ \hline 1924 \end{array}$$

At base of post deposit a marked(x)stone,  $1 \times 2 \times 3$  ins.

44.60 Dry wash, 5 lks. wide, 1 ft. deep, drains N  $25^\circ$  W.

Asc. moderate rocky S. slope 35 ft. to

53.20 Rocky spur, projects NW. Desc. gentle NE. slope 35 ft. to

58.00 Dry wash, 4 lks. wide, 6 ins. deep, drains N  $25^\circ$  W.

Asc. gentle SW. slope

67.00 Slight descent of general NE. slope

83.95 Intersect 4 th Standard Parallel North, S  $89^\circ 54'$  E.,

7.11 chs. from the std.  $\frac{1}{4}$  sec. cor. of secs. 32, and at point of intersection

Set an iron post, 3 ft. long, 2 ins. dia., 27 ins. in the ground, for closing cor. of secs. 5 and 6, with brass cap mkd