

INDEPENDENT RESURVEY OF PORTION OF W. BOUNDARY

T. 21 N., R. 47 E.

CHAINS

Set an iron post, 3 ft. long, 2 ins. dia., 27 ins. in the ground, for the cor. of secs. 13 and 24 only, with brass cap, mkd

T21N
R46E R47E
S13
S18
S24

1924

Raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor. Land, gently rolling. Soil, gravelly clay loam. Timber, none. Undergrowth, sagebrush and shadscale. Poor grazing. General drainage, NE.

SURVEY OF PORTION OF W. BOUNDARY T. 21 N., R. 47 E.

I begin at the Std. cor. of Ts. 21 N., Rs. 46 and 47 E.,

(set in survey of Group No. 36) which is a 3 in. iron post, firmly set in a mound of stone, marked and

witnessed as described by the Surveyor General. This

cor. becomes the Std. SW. cor. of T. 21 N., R. 47 E.,

therefor, I destroy markings on bearing tree to NW, and change markings on iron post to read as follows:

SC
T21N
R47E
S31
T20N R46E
S1
1924

From which

A pinon pine, 10 ins. dia., bears N 20° E., 30 lks. dist.,

mkd. T21NR47ES31SCBT

No other trees within limits in sec. 31

Thence

North, on randomline along W. bdy. of Twp., setting temp.

½ sec. and sec. cors., at regular intervals of 40.00 and 80.00 chs., and at

241.04

Fall 83 lks. W. of the cor. of secs. 13 and 24

The bearing of this line is therefor, N 0° 12' E.

From the Std SW. cor. of T. 21 N., R. 47 E.

N 0° 12' E., on true W. bdy.

Desc. steep rocky NE. slope through heavy timber 110 ft.