

SURVEY OF PORTION OF W. BOUNDARY T. 21 N., R. 47 E.

CHAINS

Set an iron post, 3 ft. long, 2 ins. dia., 27 ins. in the ground, for cor. of secs. 18 and 19, with brass cap mkd

T21N
 R46E | R47E
 S18

 S19
 1924

Raise a mound of stone, 2 ft. base, 1½ ft. high, E. of cor. Land, gently rolling. Soil, clay loam. Timber, none. Undergrowth, sagebrush. Fair grazing. General drainage, NE.

N 0° 12' E., on true W. bdy. of sec. 18
 Over sagebrush flat

1.04 Cor. of secs. 13 and 24
 Land, level. Soil, clay loam.
 Timber, none. Undergrowth, sagebrush.
 Fair grazing. General drainage, NE.

SURVEY OF PORTION OF N. BOUNDARY T. 21 N., R. 47 E.

I begin at the cor. of Ts. 21 N., Rs. 47 and 48 E., which is an iron post, firmly set in the ground, marked and witnessed as described by the Surveyor General

Thence

West on a random line along N. bdy. of tp., setting temp. ¼ sec. and sec. cors., at regular intervals of 40.00 and 80.00 chs., and at

239.10 Fall 21 lks. S. of the cor. of secs. 33 and 34
 The true bearing of this line, is therefor N 89° 57' W
 From the cor. of Ts. 21 N., R. 47 and 48 E N 89° 57' W., on true N. bdy. of tp.
 Over rough mountainous land through timber

Descend 175 ft. to

7.30 Draw, drains N., thence across flat spur

19.70 Top of flat spur, projects N. Descend

27.50 Draw, drains N 30° E. Ascend

38.10 Ridge, bears N and S. Steep descent of SW. slope 600 ft. to draw