


Independent Resurvey of the West Bdy. of T. 25 N., R. 47 E.

Chains

- 4.10 Rocky spur, 50 ft. above sec. cor., projects W. 5 chs. thence NW. Desc. NW. slope.
- 6.90 Small draw, 50 ft. below spur, drains NW., asc. rocky SW. slope.
- 16.00 Enter heavy timber, bears SE. and W.
- 23.00 Rocky point of spur, 185 ft. above draw, projects W. from a prominent black basaltic dome about 15 chs. East. Continue along rugged W. slope.
- 34.50 Head of small draw, drains W., asc. gradual SW. slope.
- 40.00 On rocky SW. slope, 80 ft. above draw, Set an iron post, 3 ft. long, 1 in. diam., 8 ins. in the ground to solid rock and 20 ins. in a mound of stone, 3 ft. base, for the  $\frac{1}{4}$  sec. cor. of secs. 1 and 6, with brass cap mkd:



from which,

A pinon pine, 8 ins. diam., bears S.73°E., 76 lks. distant, mkd:  $\frac{1}{4}$  S6 BT

A pinon pine, 8 ins. diam., bears N.41°W., 71 lks. distant, mkd:  $\frac{1}{4}$  S1 BT

No trace of the old  $\frac{1}{4}$  sec. cor. Continue over rocky SW. slope.

- 43.50 Rocky spur ridge, 30 ft. above  $\frac{1}{4}$  sec. cor., projects N. of W. from S.60°E., desc. abrupt N. slope. Leave heavy and continue thru scattering timber.
- 59.00 Enter thicket of very heavy timber and dense undergrowth.
- 70.00 Leave thicket of heavy timber, bears NW. and SE.
- 74.00 Dry wash, 8 ft. wide, 3 ft. deep, in bottom of draw 770 ft. below ridge, drains NW., asc. rocky SW. slope thru scattering timber.
- 83.00 Rounded top of spur, 100 ft. above draw, projects W., desc. gradual NW. slope.
- 90.31 At this point, on a steep NW. slope 60 ft. below spur, which I subsequently determine to be West, 34.83 chs. distant from the Std. cor. of T. 26 N., Rs. 46 and 47 E., and described in Book "A", T. 26 N., R. 47 E.,